



GD 335-S

E-NR: 6332528

Glass Break Detector, Glued



The GD 335-S has the same features as the GD 335 with transistor output and can be directly connected to a control panel via the junction box JB 103-4. The detector has a coiled cable with modular connector that plugs into the junction box JB 103-4, which allows it to be quickly and easily disconnected from the detector loop when, for example, cleaning windows.

For laminated glass use GD 475.

TECHNICAL DETAILS

Approvals	Class 2, EN 50131-2-7-2:2013 Grade 2, SBSC 10-32
Supply voltage	5-15 VDC
Alarm indication	LED
Operating temperature	-40 – +70°C
Housing protection class	IP 67
Product type	Detectors
Dimensions (L x W x H) mm	91 x 31 x 23
Environment	Indoor, Outdoor
Dimensions (L x Ø) mm	11 x 27
Product group	Glass break
Product feature	Adhesive-mounted, Surface-mounted
Security certification and approval schemes	EN, FG, SBSC, VdS
Security class	2, B
Environmental class	IIIA



ORDER INFORMATION

Model	E-NR	Description
GD 335-S	6332528	Glass break detector with transistor output, glued, coiled cable with 4-pin modular connector plug
GD 335-SJ	6332529	Glass break detector with transistor output, glued, coiled cable with 4-pin modular connector plug and junction box JB 103-4

SCHEMATICS

