



GD 330-S

E-NR: 6332523

Glass Break Detector, Glued



The GD 330-S has the same features as the GD 330 with relay output and can be directly connected to a control panel via the junction box JB 103-6.

The detector has a coiled cable with modular connector that plugs into the junction box JB 103-6, which allows it to be quickly and easily disconnected from the detector loop when, for example, cleaning windows.

For laminated and tempered glass please use GD 370 or GD 470.

TECHNICAL DETAILS

Approvals	EN 50131-2-7-2:2013 Grade 2, VdS class B – G192531
Supply voltage	8-15 VDC
Alarm output	NC
Contact rating	50 VDC / 100 mA
Alarm indication	LED
Housing protection class	IP 67
Product type	Detectors
Dimensions (L x W x H) mm	91 x 31 x 23
Environment	Indoor, Outdoor
Dimensions (H x Ø) mm	16 x 35
Product group	Glass break
Product feature	Adhesive-mounted, Surface-mounted
Security certification and approval schemes	EN, FG, SBSC, VdS
Security class	2, B
Environmental class	IIIA



ORDER INFORMATION

Model	E-NR	Description
GD 330-S	6332523	Glass break detector with relay output, glued, coiled cable with 6-pin modular connector pluge
GD 330-SJ	6332524	Glass break detector with relay output, glued, coiled cable with 6-pin modular connector plug and junction box JB 103-6

SCHEMATICS

